

1925C

Desktop



19" CRT Touchmonitor

SPECIFICATIONS

Model		1925C
Display size & type		19" (48.2 cm), 18" (45.7 cm) viewable, FST
Dot pitch		0.22 mm
Resolution presets		640 x 480 at 60 Hz 800 x 600 at 85 Hz 1024 x 768 at 85 Hz 1280 x 1024 at 85 Hz 1600 x 1200 at 75 Hz
Weight (approx.)	actual	53 lbs (25 kg)
	shipping	58 lbs (27 kg)
Display area dimensions	horizontal	14.4" (367 mm)
	vertical	10.9" (276 mm)
Monitor dimensions	width	17.6" (447 mm)
	height	17.9" (455 mm) (removable base)
	depth	18.2" (462 mm)
Scanning frequency	horizontal	31–93.75 kHz
	vertical	50–160 Hz
Video bandwidth		200 MHz
Input video power connector	external	Mini D-Sub 15-Pin (female)
Elo touchmonitor driver	serial	Compatible with all Elo PCdrivers
Power		120–240 VAC, 50/60 Hz, 135 W (max.)
Warranty		2 years monitor, 5 years touch controller
Additional features		Digital on-screen display controls MPR II, ENERGY STAR, VESA DPMS, VESA DDC 1/2B Plug and Play, ISO 9241/3 Detachable tilt swivel base

ORDERING INFORMATION

iTouch

Touchscreen Technology	Touch Interface	Surface Treatment	Elo Part Number	Agency Approvals
iTouch (touch-on-tube)	Serial	Antireflective	608501-000	UL, cUL, FCC, CE, TUV-GS

- Users should independently evaluate the suitability of the product for their application.
- All prices, models, and availability subject to change without notice.
- Stock quantities may be limited. Larger quantities are available within one week.
- For Product Agency Certifications refer to our Web site.

entuitive
Touchmonitors

ēlo
TOUCHSYSTEMS